

ROSBACK COMPANY

Manufacturer of Quality Handcrafted Bindery & Finishing Equipment since 1881

Rosback 202 Stitcher Stagger Stitch Setup Instructions

Setup Instructions:

1. Cycle machine until reference two (2) in upper picture connecting rod is horizontal or level with floor.
2. Loosen set screws in reference four (4) lower picture crank plate and disengage gears, reference five (5) from reference three (3).
3. Check the eccentric pin and be sure scratch mark on pin is at top or twelve o'clock in this position, and its setscrew is tight.
4. Re-mesh the gears in two (2) and tighten setscrews in crank plate and check for stagger.
5. Cycle machine once and place pencil mark on saddle plate at rear most position of feed finger (feed finger carries book to stitching position). Cycle machine one more time and place pencil mark, as before. If feed finger returns to first pencil mark, flip red bracket to other side of gearbox. If second pencil mark is about 5/8 of an inch from first pencil mark, you have now set stagger stitch.
6. If second pencil mark is quite short of 5/8 of an inch, you may be one or more gear teeth off from best setting.

Shipping & Mailing Address: 125 Hawthorne Ave., St. Joseph, MI 49085

Phone: (269) 983-2582 * Fax: (269) 983-2516 * Internet: www.rosbackcompany.com * E-mail: rosbacksales@qtm.net

Manufactured in the USA since 1881