

TrueLine Series PERFORATORS/SCORERS/SLITTERS

Model 218 *Bobcat* Table Top Perforator

ROSBACK

Rosback has been providing world class perforating and slitting solutions since 1881.

Where space is of the essence, this 218 True Line Tabletop Perforator offers that and more. Built with the structural integrity and performance capabilities that are synonymous with the name "True Line". Get accurate and quality performance for your short run needs.

TrueLine Perforators are designed for quality production. Get precision perforating, scoring and slitting on stocks ranging from 9-lb. onionskin to 1/16" board. TrueLine owners talk about the simplicity of operation and years of trouble free performance.


STATE-OF-THE-ART PERFORMANCE FEATURES:

- Table Top space saver
- Versatile - can slot & knife-cut perforate, score, micro perf & slit
- Quiet & simple to operate
- Quickly add or remove heads
- Quick lateral guide adjustment
- Run up to 5 heads
- Perf heads w/ built-in chip remover
- Strippers – completely surround perf cutters
- Molded drive rollers
- Variable speeds up to 15,000 fph
- See-through safety cover
- Push-to-engage hand wheel
- Handles materials ranging from 9-lb. onionskin to 1/16" board
- Low maintenance


Your Dealer:

218 STANDARD EQUIPMENT:

- 1-Set of Slot Perf Heads w/Burr Rollers
- 1-Set of Scoring/Creasing Heads
- 2-Sets of Drive Rollers
- 4-Perforating Blades
- 1-Tool Kit




Quick-Lock & Micro Adjust Side Guides for Fast Setups



Positive Feeding Caliper



Pitch Depth Control & Safety Hand Wheel



Magnetic Side Guides aid quick setup

ACCESSORIES:

- Quick-Align Perforating Heads
- "CD" inlay heads
- Gutter slitter/perf heads
- Knife-cut heads
- Micro-perf heads
- Slitting heads
- Narrow margin perf heads (3/8" from sheet edge)
- Scoring heads (Special Extra Wide)
- Special Slot-perf heads (1/2" between perf lines)
- Special Engineered Heads upon request



Standard Precision Rosback Heads

218 Bobcat TableTop Specifications

Sheet Sizes	
Minimum	2.5" (6.3cm) x 3" (7.6cm)
Maximum	18" (45.7cm) x 18" (45.7cm)
Dimensions	
Length	42" (106.6 cm)
Width	27" (68.5 cm)
Height	10.5" (26.6 cm)
Weights	
Net	100 lbs (45.3 kg)
Shipping	140 lbs (63.5 kg)
Export	190 lbs (86.2 kg)
Electrical	
Standard*	120vac, 60 Hz, 1Ph, 4amp
Cycle Speed	
Feet per hour	Up to 15,000
Minimum Spacing Between Lines	
Perforating	3/4" (1.9 cm) standard [1/2" (1.3 cm) available]
Scoring/Creasing	1/4" (6.4 mm) Standard

*Contact Rosback for alternate electrical requirements

Design Specifications Subject To Change Without Notice

ROSBACK CO.

125 HAWTHORNE AVE., ST. JOSEPH, MI 49085 USA

Phone: (269) 983-2582 * Fax: (269) 983-2516 * Internet: www.rosbackcompany.com * E-mail: Sales@RosbackCompany.com