

ROSBACK COMPANY

Maintenance & Lube Schedule for 706 & 724 Feeders

WARNING!

Make sure the input power is OFF and that disconnect is locked and tagged before starting any service or maintenance work. Do this to avoid the possibility of harm by becoming entangled in a moving part or by a severe, possibly fatal electrical shock. Be sure to follow this warning when carrying out the lube and mechanical schedules.

Preventative Maintenance & Lube Schedule

Schedule	Action	Description
Daily	Keep metal surfaces clean, free from dust, and rust.	A light coat of SAE 10 oil may be added to the metal surfaces that do not come in contact with the paper stock. It is a good idea to cover the perforator when it is not in use to keep dust from settling in working parts.
Weekly	Check condition of sucker cups and crown retainers at each pocket.	Replace damaged, cracked, or hardened cups. Replace bent or deformed crown retainers.
Weekly	Verify air flow from each air blast nozzle at each pocket.	If air flow is poor or not flowing, use a fine gauge wire to clean air blast nozzle.
Monthly	Clean and lubricate primary and secondary chains.	Clean chains with a light coat of SAE 30 oil.
Monthly (724 only)	Clean and lubricate primary and secondary chains.	Clean chains with a stiff nylon brush to remove dirt and paper dust. Relubricate using SPRAYON LUBRICANTS #S00708 T.F.E. DRY LUBE or similar, plastic safe, T.F.E. dry lubricant.
Monthly (724 only)	Lubricate suction bar pivot shaft bushings (16 locations)	Apply a drop or two of SAE-30W oil to the bushings supporting these shafts.
Monthly (724 only)	Lubricate serpentine belt tensioners under lower R.H. guard (2 locations).	Use a grease gun to apply NLGI grade 2 grease directly into grease fitting
Monthly (724 only)	Lubricate stub shaft housings under lower R.H. guard (1 location) and behind the rear lower cover (2 locations).	Use a grease gun to apply NLGI grade 2 grease directly into grease fitting
Monthly (724 only)	Lubricate mounted bearings behind the rear lower cover (2 locations).	Use a grease gun to apply NLGI grade 2 grease directly into grease fitting
Quarterly	Inspect vacuum pump filters.	Clean or replace all vacuum pump filters.