



Lamibind 420

ROSBACK

Specifications:

Machine Model:	Lamibind 420
Dimensions of the Machine:	54 x 19 x 42 in (1380 x 500 x 1080 mm)
Dimensions of the packaging:	59 x 30 x 49 in (1510 x 780 x 1250 mm)
Net Weight:	550 lb (250 kg)
Shipping Weight:	770 lb (350 kg)
Current:	16 A
Power:	3.2 kW
Power Supply:	220/230V 60Hz 3PH
Maximum Document Length:	16.5 in (420 mm)
Minimum Document Length:	5.12 in (130 mm)
Maximum document thickness	2.0 in (50 mm)
Cycle Time Without Document:	450/Hour
Number of Bindings per Hour:	260/Hour
Volume of Glue Container:	1 qt (1liter)
Heat-Up Time:	30 Minutes
Glue Melting Temperature:	280-390 °F (140-200 °C)
Glue Temperature in Standby Mode:	250 °F (120 °C)
Vise Operation:	Electric
Start After Vise is Closed	Automatic
Binding:	Automatic
Roughening:	Yes
Glue Cylinder:	Motorized
Glue Thickness Setting:	Manual
Glue Temp. Setting:	Push Buttons
Temperature Display:	Digital

Safety Equipment

Ready State Indication	READY
Working State Indicator	Orange Flashing Light
No Cycle Without Document	Yes
No cycle with Glue Cover Open	Yes
Error Code Indication	Yes
Emergency Stop	yes

Options

Shelf for Finished Documents:	Optional
-------------------------------	----------

The Lamibind 420 is manufactured for ROSBACK by Rigó Ltd., an ISO9002 certified manufacturer with over 17 years of experience.

ROSBACK CO.

125 HAWTHORNE AVE., ST. JOSEPH, MI 49085 USA
Phone: (269) 983-2582 * Fax: (269) 983-2516
Internet: www.rosbackcompany.com * E-mail: rosbacksales@qtm.net

Your Dealer: