



Millbind 420

**ROSBACK**

**Specifications:**

Machine Model:	Millbind 420
Dimensions of the Machine:	54 x 43 x 23 in (1380 x 1100 x 600 mm)
Dimensions of the packaging:	59 x 47 x 31 in (1500 x 1200 x 800 mm)
Net Weight:	600 lb (270 kg)
Shipping Weight:	770 lb (350 kg)
Current:	16/25 A
Power:	4,5 kW
Power Supply:	220/230V 60Hz 3PH
Maximum Document Length:	16.5 in (420 mm)
Minimum Document Length:	5.12 in (130 mm)
Maximum document thickness	2.0 in (50 mm)
Cycle Time Without Document:	450/Hour
Number of Bindings per Hour:	260/Hour
Binding Time Adjustment:	1 to 10 sec.
Volume of Glue Container:	1 qt (1liter)
Heat-Up Time:	30 Minutes
Glue Melting Temperature:	280-390 °F (140-200 °C)
Glue Temperature in Standby Mode:	250 °F (120 °C)
Vise Operation:	Electric
Start After Vise is Closed	Automatic
Binding:	Automatic
Roughening:	Yes
Glue Cylinder:	Motorized
Glue Thickness Setting:	Manual
Glue Temp. Setting:	Push Buttons
Temperature Display:	Digital

**Safety Equipment**

Ready State Indication	READY
Working State Indicator	Yellow Flashing Light
No Cycle Without Document	Yes
No cycle with Glue Cover Open	Yes
Error Code Indication	Yes
Emergency Stop	yes

**Options**

Shelf for Finished Documents:	Optional
Paper and Glue Vapor Vacuum:	Optional
Automatic Cover Sheet Feeder:	Optional
Milling	Optional 0-0.12 in (0-3 mm)

The Millbind 420 is manufactured for ROSBACK by Rigó Ltd., an ISO9002 certified manufacturer with over 17 years of experience.

**ROSBACK CO.**

125 HAWTHORNE AVE., ST. JOSEPH, MI 49085 USA  
Phone: (269) 983-2582 \* Fax: (269) 983-2516  
Internet: [www.rosbackcompany.com](http://www.rosbackcompany.com) \* E-mail: [rosbacksales@qtm.net](mailto:rosbacksales@qtm.net)

Your Dealer: