

ROSBACK COMPANY

MODEL 882



Shown with optional
887 Cover Feeder

SINGLE-CLAMP HOT-MELT PERFECT BINDER

Create Beautiful Bound Books with Ease

- **Heavy Duty Construction**
- **Accurate and Dependable Performance**
- **Fast Setup and Low Maintenance**

The Model 882 Perfect Binder is designed for medium length production runs and quick changeover, and meets the requirements for the in-plant shop, commercial printer and trade binders. The Model 882 Perfect Binder combines dependability, flexibility, and ease of operation. Consistent top-quality professional results are easily achieved.

Performance Features:

- Heavy Duty 3 HP Milling and Notching Motor
- Automatic Nipper Adjustment for Book Width
- Logic Control of Machine Functions
- Adjustable Nipper Dwell Time.
- Integrated Book Counter

AVAILABLE OPTIONS & ACCESSORIES:

- 17" (43.2 cm) Max Spine Length
- 19-1/2" (49.5 cm) Max Spine Length
- Cover Feeder (Model 887)*
- Cover Joggers* (available only with 887)
- Conveyor Delivery Table
- Padding Glue (48 lbs. box)
- Padding Attachment
- Glue (48 lbs. box)
- Fume Extractor

*Note: Purchase 882 & 887 together and get cover joggers free.

882 STANDARD EQUIPMENT:

- 10 lbs. Glue
- 1-Side Gluing Attachment
- 1-Rougher/Notching Blade
- 1-Integrated Book Counter
- 1-Drop Tray Delivery
- 1-Tool Kit
- 1-Spare Parts Kit

882 Perfect Binder Specifications	
Sheet Sizes	
Min Book Thickness	1/8" (3mm)
Max Book Thickness	2" (50mm)
Min Page Width x Spine Length	2-1/2" (63mm) x 4" (101mm)
Max Page Width x Spine Length (see options)	12" (304mm) x 15-1/2" (393mm)
Max Milling Depth	5/32" (4mm)
Dimensions	
Length (with Conveyor attached)	69" (1.75 m)
Width	84" (2.13 m)
Height	43-1/2" (1.11 m)
Weights	
Net	850 lbs. (386 kg)
Shipping	1315 lbs. (596 kg)
Export Shipping	1530 lbs. (694 kg)
Electrical*	
Standard**	230 vac, 60Hz, 3Ph, 30 amp
Speeds	
Cycle	Up to 600
Production	Up to 450 Books/Hr

*Contact Rosback for alternate electrical requirements.
Design Specifications Subject To Change Without Notice.

ROSBACK CO.

125 HAWTHORNE AVE., ST. JOSEPH, MI 49085 USA
Phone: (269) 983-2582 * Fax: (269) 983-2516
Internet: www.rosbackcompany.com
E-mail: sales@rosbackcompany.com



Mil Cutter & Notcher

Carbide cutter with built-in notcher provides for maximum glue penetration.



Nipper Table & Cover Stops

Positive stops align the book covers. Nipper plates automatically adjust for various book thicknesses.

*Optional Cover Joggers are available.



Master Control Station

Centrally located and includes book counter display.



Clamp Assembly

Adjustable clamp pressure securely holds books throughout the binding cycle.



Removable Glue Pot

Removable glue pot holds a generous glue supply and rapidly adjusts for quick setup.



Glue Pot Rollers

Twin rollers apply glue to book spines and the amount is adjustable for each roller.

